



QC STL PRO-6.0X
QuietCool Stealth Pro Line

QC STL PRO-6.0X Specifications

Air Flow	Hi: 5,587 CFM / Med: 4,262 CFM / Low: 3,428 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 4,030 CFM / Med: 3,070 CFM / Low: 2,440 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,862 SQFT to 2,794 SQFT	
Energy Use	Hi: 462 Watts / Med: 210 Watts / Low: 113 Watts	
Amps	Hi: 5.91 / Med: 2.90 / Low: 1.65	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	3	
dBA	Hi: 49.3 / Med: 42.5 / Low: 38.5	
Minimum Attic Clearance	42"	
Duct Diameter	22"	
Duct Length	9 feet	
Motor Head Diameter	22 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Included: 8 Hr Electronic Timer & Double 3-way switch Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	7.45 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	96 lbs.	
Box Dimensions	41" x 26" x 39"	
In The Box	-QC STL PRO-6.0X Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM